

Release Notes

API Name	InstaFlights Search
SOAP Service Action Code	1
REST Method/Endpoint	POST /v1/shop/flights
Enhancements	<p>A number of InstaFlights Search API enhancements were promoted to certification/production on 8/11/2016:</p> <ul style="list-style-type: none"> • enabletagging: returns a Tag ID for each itinerary in the response and stores in the Sabre cache. The tag ID can be used to retrieve an itinerary via the new InstaFlights Search - Tag ID Lookup URL. • view: use a Sabre default response view or create a custom response view. To create a custom response view, define the response paths to include or exclude using the Custom Response View API, then pass the view as a filter in the request URI, e.g., view=NOWARNINGS to format the response. See the Response View Lookup API for a list of Sabre response views. • returndate: the return date is now optional. Omit the return date to retrieve a one-way flight. • See InstaFlights Search API documentation for details.

New features

Optional	In the request
Parameter	enabletagging
Type	boolean
Description	<ul style="list-style-type: none"> • Returns a TagID for each itinerary and stores in the Sabre cache <ul style="list-style-type: none"> ◦ The tag ID can be used to retrieve an itinerary from the Tag ID Lookup URL at: GET /v1/shop/flights/tags/{tagid}. • See documentation for new methods and endpoints.
Sample Value	enabletagging=true – returns and stores itineraries for subsequent calls to the Sabre cache
Parameter	view
Type	string

Description	The response view definition
Sample Value	<ul style="list-style-type: none"> view=IF_ITIN_TOTAL_PRICE – a Sabre response view that excludes numerous response paths for the InstaFlights Search API view=BFM_ITIN_TOTAL_PRICE – a Sabre response view that excludes numerous response paths for the Bargain Finder Max API
Note	You can either use a Sabre default response view or create a custom response view using the Custom Response View API.
Parameter	returndate
Type	string
Description	Date of returning flight in the time zone of the destination airport
Sample Value	Returndate=2016-08-31
Note	Previously, the return date was required.

New features

N/A

In the response

Element	TagID
Type	string
Description	The tag ID for the respective itinerary
Note	<ul style="list-style-type: none"> A tag ID is returned when enabletagging=true is used in a previous InstaFlights Search API request The tag ID can be used to retrieve an itinerary from the Tag ID Lookup URL See documentation for details on tag ID expiration values.
Element	Links
Type	array
Element	tagLookupLinkTemplate

Type	N/A
Description	Formats an API request with placeholders to retrieve the itinerary associated with a given tag ID
Note	N/A

Resolved issues

Description	This release does not contain any bug fixes.
-------------	--